

# Plusrite®

## LED FLOOD LIGHT





Unit: MM




AU01-FL10W/B/3K/12V 3M  
AU01-FL10W/B/5K/12V 3M




AU01-FL10W/POLE



Net Weight: 0.55 kg  
Outer ctn size: 510\*410\*410mm  
Q'ty per ctn: 18 pcs  
G.W per ctn: 15 kg



FL10W-SOS-PB



### Feature:


1. 4400mAh power bank supply.
2. SOS mode for emergency.
3. backup magnets ensure your hands free while working.
4. Unique design and lightweight.
5. Input: 5V DC 1A,  
Output: 5V DC 2.1A(max).

### Instruction:

1. Power button:  
Press the power button for maximum brightness mode,  
Press again for power saving mode,  
Press and hold for two seconds to turn off.
2. SOS button:  
Press the SOS button for SOS mode.  
Press again to turn off.
3. LED indicator light:  
It stays red when charging and  
turns green after being fully charged.
4. When battery is low, the indicator light will flash red.



MFL-400-90D-5K



Unit: MM




Net Weight: 14.5 kg  
Outer ctn size: 740\*430\*180mm  
Q'ty per ctn: 1 pc  
G.W per ctn: 16.4 kg



LUX-PLS-1000



Bullseye



Unit: MM

Net Weight: 25 kg  
Outer ctn size: 750\*650\*550mm  
Q'ty per ctn: 1 pc  
G.W per ctn: 31 kg

## TECHNICAL SPECIFICATIONS

Model.	CHIPS TYPE	Colour Temperature	Voltage (V)	Beam Angle	Wattage (W)	Luminosity (lm)	Flex-In-Plug	Housing colour	Warranty	IP RATING	Dimmable
AU01-FL10W/B/3K/12V 3M	COB	3K	AC12V/DC12V	120°	10W	800lm	3 Meters/12V connection	Black	3 years	IP65	NO
AU01-FL10W/B/5K/12V 3M	COB	5K	AC12V/DC12V	120°	10W	850lm	3 Meters/12V connection	Black	3 years	IP65	NO
AU01-FL10W/POLE	Garden Pole for 10W Flood light										
FL10W-SOS-PB	COB	6K	DC 5V	120°	10W	400lm	NO	Black	1 year	IP65	YES
MFL-400-90D-5K	SMD	5K	180-240V	90°	400W	52000lm	NO	Black	5 years	IP65	NO
LUX-PLS-1000	SMD	3K/4K/5K/6K	100~305V	10°/15° 30°/60°	1000W	115000lm	YES	Black	5 years	IP65	DALI/1-10V
BULLSEYE	Accessory for LUX-PLS-1000(optional)										

