

Product Code:MHCA/0007-MHCA-0008

Description: CMP70W/T/830/G12/Clear/Europe-CMP70W/T/942/G12/Clear/Europe

Product Name: Ceramic Metal Halide Lamps

Technical Performance Data Sheet

MHCA/0007: CMP70W/T/830/G12/Clear

Light Output (Lumens/100Hrs)	7000/6500
Lamp Lumens Per Watt	100/93
Mean Output (Lumens)	6000/5700
Rated Life (Hours)	15000
Color Temperature (k)	3000K/4200K
Chromaticity (CIE-x/y)	NA
Color Rendering Index (CRI)	80/90
To 90% Warm Up Time (Minute)	2 to 3 Minutes
Hot Restart Time (Minute)	10 to 15 Minutes
Burning Position	UNIVERSAL



Physical Data/ Requirements

Base Designation	G12
Bulb Designation	Tubular UV-STOP
Bulb Diameter mm	19±1/mm
Max Overall Length (MOL) mm	90mm
Light Center Length (LCL) mm	56±1/mm
Effective Arc Length	3.8mm
Max Base Temperature	280°C
Max Bulb Temperature	490°C
Luminaire type	ENCLOSED
Socket Pulse Rating (V)	3500-4500V

MHCA/0008: CMP70W/T/942/G12/Clear



Electrical Data/ Requirement

Lamp Wattage (W)	70W
Operating Voltage (V)	90V
Operating Current (Amps)	0.98A
Min. Open Circuit Voltage (RMS)	210V
Min Max Starting Pulse (Peak v)	3500-4500V
Min Pulse Width (u sec)	1
Min Pulse Rate Per 1/2 Cycle	1
Pulse Position (Min.% OCV Peak)	60° ~ 90°
Revision :	17/09/2012

This lamp can cause skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured.

Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used, *This is for reference, not the absolute standard.