

Product Code:MHCA/0014-MHCA/0015

Description: CMP35W/Par20/830/SP/E27/Clear/Europe-CMP35W/Par20/830/FL/E27/Clear/Europe

Product Name: Ceramic Metal Halide Lamps

Technical Performance Data Sheet

MHCA/0014: CMP35W/Par20/830/SP/E27/Clear

Center Intensity	22000/7500
Beam Angle	SP10Deg/Flood/25Deg
Rated Life (Hours)	10000
Color Temperature (k)	3000K
Chromaticity (CIE-x/y)	NA
Color Rendering Index (CRI)	80
To 90% Warm Up Time (Minute)	2 to 3 Minutes
Hot Restart Time (Minute)	10 to 15 Minutes
Burning Position	UNIVERSAL



Physical Data/ Requirements

Base Designation	E27
Bulb Designation	Par20
Bulb Diameter mm	65mm
Max Overall Length (MOL) mm	86mm
Light Center Length (LCL) mm	NA
Effective Arc Length	4mm

MHCA/0015: CMP35W/Par20/830/FL/E27/Clear

Max Base Temperature	280°C
Max Bulb Temperature	490°C
Luminaire type	OPEN
Socket Pulse Rating (V)	3500-4500V



Electrical Data/ Requirement

Lamp Wattage (W)	35W
Operating Voltage (V)	85V
Operating Current (Amps)	0.53A
Min. Open Circuit Voltage (RMS)	NA
Min Max Starting Pulse (Peak v)	3500-4500V
Min Pulse Width (u sec)	1
Min Pulse Rate Per 1/2 Cycle	1
Pulse Position(Min.% OCV Peak)	60° ~ 90°
Revision :	17/09/2012

This lamp can cause skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured.
 Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used, *This is for reference, not the absolute standard.