
Plusrife® AUSTRALIA PTY LTD

SOLAR WALL PACK LIGHT RANGE

PLS-WP-7W & PLS-WP-13W &




perimeters. It eliminates ongoing costs and offers a durable, low-maintenance lighting solution built for commercial use.

KEY ADVANTAGES

- Zero running costs and high efficiency
- Highly versatile power and colour options
- Flexible placement and installation for any location
- Durable construction featuring
 IP65 and IK08 impact rating
- Premium technology made for reliability, efficiency, and lifespan













SOLAR WALL PACK LIGHT RANGE

PLS-WP-7W & PLS-WP-13W &

TECHNICAL SPECIFICATIONS

Solar Panel

Rated Wattage

Lumens

Battery Type

Measurements

Weight

Cable Length

CCT Switchable

CRI(Ra)

LM80

Beam Angle

Charging Time

Discharge Time

IK Rating

IP Rating

Operating Temp.

Working Mode

PLS-WP-7W

25W Bifacial Mono

5W or 7W

1,150LM - 1,840LM

12.8V/12AH LiFe PO4

L27 x W20 x H15cm

4KG

PLS-WP-13W

25W Bifacial Mono

9W or 13W

2,300LM - 3,450LM

12.8V/24AH LiFe PO4

L51 x W20 x H15cm

9KG

Both Models

3 Metres

3,000K or 5,000K

>70

>50,000 Hours

120°

4 - 7 Hours

14 - 24 Hours

IK10 / Vandal Proof

IP65

-10°C - 65°C

4 Switchable Operating Modes

1H 100%, 1H 80%, 2H 60%, 5H to dawn 20%

5H 100% then off

4H 100%, 5H to dawn 20% 100% from dusk to dawn